



NOTES:

1. STOP SIGN PLACEMENT SHALL BE AT RADIUS, WHEN POSSIBLE (6' MINIMUM / 30' MAXIMUM FROM THROUGHFARE).
2. AT CURBED LOCATIONS, SIGN SHALL BE 2' FROM EDGE OF SIGN TO FACE OF CURB. AT UNCURBED LOCATIONS, SIGN SHALL BE 6" TO 12" FROM EDGE OF PAVEMENT. WHERE SIDEWALK ABUTS CURB, SIGN SHALL BE PLACED IN SIDEWALK AS SHOWN.
3. STOP BAR AND STOP SIGN SHALL BE PLACED ADJACENT TO EACH OTHER, WHEN POSSIBLE. WHEN A CROSSWALK IS PRESENT, THE STOP BAR SHALL BE PLACE 4' CLEAR FROM CROSSWALK STRIPING.
4. FLAT BLADE: ALCOA #86054.6063-T6 ALLOY, ETCHED, DEGREASED WITH #1200 ALODINE FINISH WITH #3877 GREEN HIGH INTENSITY BACKGROUND AND EQUAL DIMENSIONS - 9" & 12" MIN. H, 24", 30" OR 36" L.
5. LETTERS: NAME - 6" & 9" SERIES 'B' # 3870 HIGH INTENSITY (SILVER) OR EQUAL - SUFFIX - 4.5" SERIES AS ABOVE.
6. 9" BLADES WITH 6" LETTERS FOR TWO LANE ROADS WITH A SPEED LIMIT UNDER 45 MPH.
7. 12" BLADES WITH 9" LETTERS:
 - THOROUGHFARE ROADS FOUR LANES OR WIDER.
 - TWO LANE ROADS WITH A POSTED SPEED LIMIT OF 45 MPH OR MORE.
 - ONLY ONE BLADE WILL BE USED INDICATING THE SIDE STREET NAME.



**CITY OF LAKE WORTH
PUBLIC SERVICES DEPARTMENT**

STOP SIGN AND STOP BAR

DETAIL NO.
09
ISSUED: 09/18/13